



Implementation and Maintenance of Human Resource Management System (HRMS)

Biometric Installation

Version 1.0

Jan 15, 2021



KELLTON TECH

Revision History

Core HR			
Version No.	Date	Version Detail	Author
1.0	Jan 15, 2021	Initial Draft	Sanjay Tiwari

TABLE OF CONTENTS

1. Safety Instructions	3
2. Installation.....	3
3. Operaion.....	3
4. Introduction.....	4
5. Wall Mount	5
6. Internet Connection.....	5
6.1. LAN	5
6.2. WIFI.....	5
7. Power Supply	6

1. Safety Instructions



Noncompliance of instructions to use the product leads to injury or loss.

2. Installation

Do not install the product in direct sunlight, moisture, dust and open area.

Do not install the product in place with heat.

Install the product in a dry and safe place.

The user should not install or repair the product independently.

Use the separate power supply for the biometric device.

Proper installation of LAN cable or WIFI connectivity.

3. Operation

Do not allow liquids, beverages or any chemicals get into the product.

Do not drop the product.

Do not contaminate or damage the fingerprint contact unit with a dirty hand.

Clean the product with a soft and dry cloth without water and wipe gently.

Do not move the product after installation otherwise scanner problem occurs.

4. Introduction



PVC Anchor



Fixing Screw



DC Power Supply Adapter



LAN Connector



Lock Key

5. Wall Mount

Determine the correct position to mount the biometric device. Fix the biometric device using PVC anchor and fixing screw.



6. Internet Connection

6.1.LAN


Connect the device to the internet using general type LAN Cable



6.2.WIFI


Connect the device to the internet using wifi connection.

Go to setting >> Network and Internet >> Wi-Fi and click on “On” and choose the WIFI from the list and enter password. Click on “CONNECT”, device will be connected with internet. You can find **WIFI** option on the home screen, just swipe down on the top.



7. Power Supply

Open the biometric device and connect the DC power supply adapter in the tablet installed in the device.



Connect the DC power supply adapter to the power socket.



Switch on the device.

Thank you.